

Polysafe Hydro

PRODUCT SPECIFICATION

Key Features

- > Pimple emboss safety flooring for barefoot & shod use
- > Sustainable slip resistance, 36+ Pendulum Test (slider 96)
- > Thermally welded seams for an impervious finish
- > Ideally suited for continually wet areas walk-in showers & hydrotherapy areas



Product Format	Standard	Result		
Gauge	ISO 24346 (EN 428)	2.0mm		
Total Weight	ISO 23997 (EN 430)	2910g/m ²		
Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	8	-	40m ²
Performance Requirements	Standard	Result		
General Performance	EN 13845 ASTM F1303	Conforms Type II, Grade I, Class B Backing		
Use Area	ISO 10874 (EN 685)	23, 34, 43		
Enhanced Slip Resistance	EN 13845 RRL Pendulum Test DIN 51097 / DIN EN 16165 Ann. A DIN 51130 / DIN EN 16165 Ann. B Surface Roughness ASTM D2047 AS 4586 Appendix C	ESb & ESf ≥36 (wet test - Slider 55/96) Class B R10 Rz ≥20µm SCOF ≥0.8 Class B		
Abrasion Resistance	EN 13845	50,000 cycles		
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2	Class Bfl-S1 Class 1 FSV < 300; SDV < 500		
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'		
Water Tightness	EN 13553	Annex A		
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750psi)		
Flexibility	ASTM F137	1.5" Pass		
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets		
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets		

Sustainability	Standard	Result
BRE Green Guide		A+ ENP 472
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		Contains recycled material
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth



BS EN 14041

EN 14041

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.


Polysafe Hydro




RANGE SHADES




White Stone H4930 w/r 4930
NCS S 2000-N LRV 44




Bisque H4860 w/r 4860
NCS S 2002-Y50R LRV 46



Sheared Slate H4960 w/r 4960
NCS S 4010-B50G LRV 26




Oystershell H4800 w/r 2010
NCS S 3010-Y60R LRV 34




Tempered Steel H4940 w/r 4940
NCS S 4502-B LRV 25



Woodland Grey H4770 w/r 9120
NCS S 4500-N LRV 28



Blue Forge H4850 w/r 4850
NCS S 5030-R70B LRV 9



Marine H4870 w/r 4700
NCS S 4030-B LRV 19

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Ltd. Head Office

PO Box 3, Radcliffe New Road, Whitefield, Manchester, M45 7NR • Tel: +44 (0) 161 767 1111 • Email: info@polyflor.com • www.polyflor.com

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.